

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
11 November 2004 (11.11.2004)

PCT

(10) International Publication Number  
**WO 2004/096406 A1**

(51) International Patent Classification<sup>7</sup>: **B01D 17/038,**  
E21B 43/38

[US/US]; 8051 Port Douglass Cove, Cordova, TN 38018 (US).

(21) International Application Number:  
PCT/US2003/023311

(74) Agent: **LONDA, Bruce, S.**; Norris, McLaughlin & Marcus, P.A., 220 East 42nd Street, 30th Floor, New York, NY 10017 (US).

(22) International Filing Date: 24 July 2003 (24.07.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
PCT/US03/09014 26 March 2003 (26.03.2003) US

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(71) Applicant (*for all designated States except US*): **GNESYS, INC.** [US/US]; 2147 Frisco Avenue, Memphis, TN 28144 (US).


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,

(72) Inventor; and

(75) Inventor/Applicant (*for US only*): **NASSIF, Naji**

[Continued on next page]

(54) Title: HYDROCYCLONE FOR DOWN-HOLE USE



(57) Abstract: Hydrocyclone (1) for separating an input stream (8) of two immiscible liquids having a stream inlet (18) an inner shell (3) and an outer shell (4) concentric with the longitudinal axis (5) of the hydrocyclone (1), a cyclone chamber is defined by the shells (3,4), encircles the axis (5) and has an entrance (7), an expansion chamber (9) which reduces the velocity of the input stream (8) by the time it reaches the entrance (7) is between the stream inlet (18) and the entrance (7). The dimensions of the hydrocyclone are selected so that the hydrocyclone (1) has a radius not more than 30% greater than the radius of the outer shell (4) and lies within a circle in a plane perpendicular to and centered on the axis (5), therefore the hydrocyclone (1) can be readily lowered into a well casing (2) in the ground.